

EQUO SOFT LIGHT



Addolcitore completo
Complete water softener



DESCRIZIONE

Gli addolcitori EQUO SOFT LIGHT utilizzano una bombola in VTR e si avvalgono di una centralina computerizzata che fornisce all'utente tutte le informazioni sulla programmazione. Sono provvisti di valvola Runxin F79 e connessioni da 1/2", sistema automatico di rigenerazione delle resine, in modalità TEMPO/VOLUME. By-PASS fornito di serie.



DESCRIPTION

EQUO SOFT LIGHT water softeners feature a computerised control unit which provides the user with all information on their programming etc. They are equipped with F79 Runxin valve and inlet size 1/2", automatic resin regeneration systems, in TIME/VOLUME mode. Pressure vessel inside the EQUO SOFT LIGHT is in FG. By-PASS included as standard.

EQUO SOFT LIGHT MINI

Codice/Code	Modello/Model	Formato bombola Pressure vessel size	Capacità Resina (Lt) Resin capacity (Lt)	Capacità ciclica (M3 /°F) Cyclic capacity (M3 /°F)	Consumo medio di sale per rigenerazione (Gr) Average salt consumption per regeneration (Gr)	Portata consigliata (m3 /h) Flow-Rate recommended (m3/h)	Imballo Pack
A9980020PK	Equo Soft Light Mini	8"x17"	8,0	44,0	1200	1,0	420x620x700h
A9980025PK		10"x17"	13,0	71,5	1950	1,5	420x620x700h

EQUO SOFT LIGHT MAXI

Codice/Code	Modello/Model	Formato bombola Pressure vessel size	Capacità Resina (Lt) Resin capacity (Lt)	Capacità ciclica (M3 /°F) Cyclic capacity (M3 /°F)	Consumo medio di sale per rigenerazione (Gr) Average salt consumption per regeneration (Gr)	Portata consigliata (m3 /h) Flow-Rate recommended (m3/h)	Imballo Pack
A9981020PK	Equo Soft Light Maxi	8"x35"	20,0	110,0	3000	2,5	420x620x1100h
A9981030PK		10"x35"	28,0	154,0	4200	3,0	420x620x1100h